

# Alcatel

## SP2503



### Color your day, go green

- **2.8" TFT Color display** for easy access to a variety of business functions through a vivid and intuitive interface
- **Paperless programmable keys** to quickly spot and reach your favorite functions and contacts
- Access to **large local and network phonebooks** for enhanced contact management
- **Headset and EHS\* support** for convenient conversations in office environments
- Embedded **VPN client** for secure remote connections



Color display



28 paperless keys (4x7)



4 sip accounts



HD voice



## MAIN FEATURES

- 2.8", 320x240 TFT color display
- 4 sip accounts
- Power over Ethernet
- Full duplex handsfree
- Wideband audio
- RJ9 headset port and headset key
- EHS support for Plantronics headsets (with APD-80)
- Call log: 100 entries (received, dialed, missed)
- Phonebook: local (500 entries, downloadable), XML, LDAP, black and white lists
- Programmable paperless keys
- Caller ID (name & number)
- Multiple built-in languages on WUI and phone MMI

## FUNCTION SUPPORT

- Call waiting, call swap, up to 10 call handling
- 8 paperless programmable line/function keys with tri-color backlight (up to 28 virtual keys)
- 4 customizable softkeys
- Programmable shortcuts in navigation keys
- Visual indicators (LED or on/screen: incoming call, MWI, mute, headset, no service)
- Mute, hold, transfer, call forward, call deflection, redial, 3-way conference
- 9 built-in melodies
- Do Not Disturb (per line and per phone), keypad lock
- Auto answer (per line)
- Volume control (handset, speakerphone, headset and ringers)
- Peer-to peer mode, IP Call
- Dial plans, prefix replacement, call barring
- Anonymous call, ACR
- XML browser, action urls, click to talk
- Keypad lock
- Hot line
- Hot desking

## IP PBX INTEGRATION

- Voicemail access, MWI
- Network conference
- BLF (list/extension)
- DND&CF sync, SCA
- Intercom, music on hold, multicast paging
- Call park, pickup
- Call completion
- Country call progress tones
- Distinctive ringing
- VIP melodies

## KEYPAD

- 4 customizable softkeys
- Configurable idle mode function for all hardkeys
- 5 way navigation key (configurable shortcuts for idle mode)
- Hold, transfer, conference, Phonebook and Call History keys
- Redial, access to voicemail keys
- Volume up and down, mute, handsfree and headset keys

## INTERFACES

- 2 RJ-45 auto sensing 10/100Mbps (LAN/PC)
- 1 RJ-9 port for handset connection
- 1 RJ-9 port for headset connection
- 5Vdc power jack

## TECHNICAL SPECIFICATIONS

### VoIP Protocol Support:

- SIPv2 (RFC3261)

### Voice Features:

- G722, G711A, G711u, G723.1, G726-32, G729ab
- Wideband audio
- Voice Activity Detection, Comfort Noise Generation, Acoustic Echo Cancellation, Packet Loss Concealment, Adaptive Jitter Buffer (300ms), AGC
- Full duplex handsfree with AEC, 96ms tail length
- DTMF: In band, RFC2833, SIP Info

### Network Features:

- DHCP/Static/PPPoE
- DNS Srv, STUN, NTP
- 802.1x, LLDP
- Port mirroring
- QoS 802.1p/Q, ToS/DSCP

### Security Features:

- TLS, SRTP, HTTPS
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- Config file AES encryption
- 2 level access privileges (user/admin)
- Password dial and Certificate management

### Industrial Standard Certifications:

- FCC, CE

## CONFIGURATION AND MANAGEMENT

### IP address Assignment:

- DHCP, static IP, PPPoE

### Configuration Support:

- Keypad
- Web browser management (Admin/User), HTTP/HTTPS
- Autoprovision with PnP, HTTP/HTTPS/TFTP/FTP, APRT support
- One-click config file generation, config restore
- TR069
- Pcap tracing, syslog

## PHYSICAL & ENVIRONMENTAL

### Mounting:

- Adjustable multiposition footstand: 2
- Desk top and wall mountable

### Power over Ethernet:

- 802.3af, class 2

### Power Adaptor:

- AC100-240V input, 5Vdc/1000mA output (not included, order separately)

### Power Consumption:

- 1.3-4.3W

### Operating temperature:

- From 0° to 40°C

### Operating Humidity:

- 10% to 60% non-condensing

### Storage temperature:

- Up to 50°C

### Package dimensions:

- 285x270x65mm (WxLxH)

## COMMERCIAL REFERENCE

SP2503

PSU for SP2503 (EU)

PSU for SP2503 (US)

3700601490015

3700601490107

3700601490114